



 36,3%



NATURAL
REFRIGERANT
R290

Key Features

The FM-480AKE-HC-SB and FM-480AKE-HCN-SB are modular ice makers, which utilise Natural Refrigerant R290.

-  Energy efficient, with savings of 36,3% compared to HFC equivalent model.*
- ✓ Produces either Flake or Nugget (-N) ice.
- ✓ Members of the Emerald Class, Hoshizaki's new range of climate friendly ice makers.
- ✓ Can produce up to 450kg of ice (flake) and 380kg (nugget) per 24 hours (AT.10°C.WT.10°C).
- ✓ Flake ice applications: food processing, fish and fresh produce display, organ transportation in medical arena.
- ✓ Nugget ice applications: packaged produce display (bottled beverages and food) and as key ingredient in beverages.
- ✓ Efficient ice making process due to Hoshizaki's unique FM auger system. Utilises all water brought into the machine; therefore water consumption is equal to ice production.
- ✓ Auger is made of double hardened stainless steel. Combined with carbon bearings, they work optimally in a tough and wet environment. Benefits include: longer product life expectancy and reduced maintenance costs.
- ✓ Electronically controlled to ensure an optimised ice making process under varying circumstances without the need for physical adjustments. Quality of ice is always consistent.
- ✓ Main characteristic of Hoshizaki's Flake ice is that 'freeze- burn' is prevented when displaying fresh fish or produce.



FM-480AKE-HC-SB
Ice: Flake



FM-480AKE-HCN-SB
Ice: Nugget

Available Models

Model	Air Cooled	Water Cooled
FM-480AKE-HC-SB	✓	
FM-480AKE-HCN-SB	✓	

Bins

Model	Type of Bin	Max. Bin Capacity approx.
B-301SA	Modular	144kg
B-501SA, Top Kit - TK 8 D		217kg
B-801SA, Top Kit - TK 8 D + TK 18 D		348kg

Production


Model	Ice Production per 24h approx.	Temperature	Water Consumption per 24h approx.
FM-480AKE-HC-SB	450kg	AT.10°C, WT.10°C	0,450m ³
	400kg	AT.21°C, WT.15°C	0,400m ³
	340kg	AT.32°C, WT.21°C	0,340m ³
FM-480AKE-HCN-SB	380kg	AT.10°C, WT.10°C	0,380m ³
	330kg	AT.21°C, WT.15°C	0,330m ³
	270kg	AT.32°C, WT.21°C	0,270m ³

For more information visit our website at www.hoshizaki-europe.com

Hoshizaki Europe B.V. retains the right to change products and their specifications without prior notice.




FM-48oAKE-HC-SB



FM-48oAKE-HCN-SB

➔ CAD drawings available on our website



Specifications

	FM-48oAKE-HC-SB	FM-48oAKE-HCN-SB
Dimensions W x D x H (mm)	560mm x 700mm x 780mm	560mm x 700mm x 780mm
AC Supply Voltage	1/220-240V 50Hz	1/220-240V 50Hz
Electric Consumption (AT.32°C, WT.21°C)	1100W	1170W
Heat Rejection (AT.32°C, WT.21°C)	2190W	2190W
Refrigerant Charge	R290	R290
Isolation	Polyurethane	Polyurethane
Weight Gross / Net	99 kg / 92 kg	99 kg / 92 kg

Operation Requirements

Ambient Temperature	5 - 40°C
Water Supply Temperature	5 - 35°C
Water Supply Pressure	0,05-0,8MPa (0,5-8bar)
Voltage Range	Rated Voltage ± 6%

Accessories

Mounting Bracket
Installation Kit